



Research Laboratory
Tel. +48 68 45 75 161 lub +48 68 45 75 163
e-mail: laboratorium@lumel.com.pl

Price list for recalibration services for Lumel SA products
Valid from 01/10/2021
LUMEL SA Research Laboratory

LUMEL SA products by type	Calibration price [EUR]	Comments
B1	52	
B2	52	
B3	52	
B4	52	
B5	52	
B6	52	
BA27	48	
BA39	48	
BE27	48	
BE39	48	
CA32	48	
CA36	48	
CA37	48	
CA39	48	
CT1	48	Price for measuring point (max. Up to 600 °C) ***
D5	48	
EA12	48	
EA16	48	
EA17	48	
EA19	48	
EB16	48	
EP27	48	
EP29	48	
FA32	48	
FA32L	48	
FA39	48	
HT20	71	The price includes: 1 x temperature 23 ° C, 1 x selected humidity point for the range from 20% to 90% RH (at 23 ° C) **
HT20IoT	71	The price includes: 1 x temperature 23 ° C, 1 x selected humidity point for the range from 20% to 90% RH (at 23 ° C) **

KD7	571	
KD8	238	
MA12	48	
MA12L	48	
MA16	48	
MA16L	48	
MA17	48	
MA17L	48	
MA19	48	
MA19L	48	
MB16	48	
N100	71	
N14	52	
N19Z	48	
N20	48	
N20Z	48	
N21	48	
N24H	48	
N24S	48	
N24T	48	
N24Z	48	
N25H	48	
N25S	48	
N25T	48	
N25Z	48	
N30H	48	
N30O	48	
N30P	48	
N30U	48	
N43	71	
NA3	71	
NA5PLUS	71	
NA6	95	
NA6PLUS	95	
NC11	48	
NC12	48	
NC14	48	
ND03	76	
ND04	76	
ND08	76	
ND1	167	
ND10	48	
ND20	62	

ND22	71	
ND25	71	
ND30	67	
ND30BAC	67	
ND30IoT	67	
ND30PNET	67	
ND40	138	
ND45	138	
NP06	167	
NP08	167	
NP10	167	
NP15	167	
NP15B	167	
NP40	214	
NP45	214	
NR30	71	
NR30BAC	71	
NR30IoT	71	
NR30PNET	62	
NS5	57	
NT10	119	
P10	48	
P10Z	48	
P15	71	
P17	48	
P17G	48	
P18	96	The price includes: 1 x temperature 23 ° C, 1 x selected humidity point for the range from 20% to 90% RH (at 23 ° C) **
P18D	96	The price includes: 1 x temperature 23 ° C, 1 x selected humidity point for the range from 20% to 90% RH (at 23 ° C) **
P18L	96	The price includes: 1 x temperature 23 ° C, 1 x selected humidity point for the range from 20% to 90% RH (at 23 ° C) **
P18S	96	The price includes: 1 x temperature 23 ° C, 1 x selected humidity point for the range from 20% to 90% RH (at 23 ° C) **
P19	96	The price includes: 1 x temperature 23 ° C, 1 x selected humidity point for the range from 20% to 90% RH (at 23 ° C) **
P20	48	
P20G	48	
P20H	48	
P20Z	48	
P21Z	48	
P30H	60	
P30O	60	
P30P	60	

P30U	60	
P41	71	
P43	71	
PA32L	38	
PA39	48	
PA39L	38	
Przekładniki prądowe LCTB	18	
Przekładniki prądowe LCTM	18	
Przekładniki prądowe LCTP	45	
Przekładniki prądowe LCTR	18	
Przekładniki prądowe LCTS	24	
Przekładniki prądowe LRC	18	
RE01	48	
RE22	48	
RE41	48	
RE42	48	
RE43	48	
RE44	48	
RE55	48	
RE60	48	
RE62	48	
RE70	48	
RE71	48	
RE72	48	
RE81	48	
RE82	48	
RE92	48	
RG14	48	
RG24	48	
RL10	48	
S4AI	48	
S4AO	48	
SM1	48	
SM2	190	
SR11	48	
T23°CT	71	

* Please provide the number / number of the measuring channel and which ranges are to be calibrated

** Please provide the humidity calibration point - in the absence of such information, calibration is carried out for 50% RH

*** Please indicate the points at which calibration should be performed